



- Recommended for the construction of sealed lighting fixtures

APPLICATION

- LED protection and light diffusion in lighting fixtures


MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	PC
Shape	flat
Maximum length on request	3000 mm
Width	21 mm
Possibility of bending	yes
UV resistance	yes

Finish	Light transmission	Length	Possibility of obtaining a line of light	Ref
frosted	65 %	1000 mm	yes	B17011F_1
		2005 mm		B17011F_2
		3010 mm		B17011F_3
clear	88 %	1000 mm	no	B17011C_1
		2005 mm		B17011C_2
		3010 mm		B17011C_3

RELATED PROFILES



LESTO
B5551

RELATED PROFILES > ARCHITECTURAL




DIPOK-US
A01233



DIPOKET
A01177



GIZA
A05556



GIZA-DUO-LL
A02162



GIZA-LL
A00758



GIZA-LL-T
A02479



GIZA-LL-UST
A02724N



GLAZA-DUO
A03059



KOZEL
A06454



KOZUS
A07823



KOZUS-CR
A00600



LARKO
A05552



LIPOD
A05554



LOC-30
A18015



LOKOM
A05553




OPAC-30
A06164

RELATED PROFILES > FACADE



FASKO
A04323

RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



KIDES-DUO
A18032



WERKIN
A18025

RELATED PROFILES > STAIRS ILLUMINATION



STEPUS
A18038