

## APPLICATION

- LED protection and light diffusion in lighting fixtures

## MOUNTING

- Snapped in a dedicated profile

## ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)  
 - when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING




## TECHNICAL SPECIFICATIONS

Material	PC
Shape	flat
Maximum length on request	10000 mm
Width	14.8 mm

Finish	Light transmission	Length	Ref
frosted	72 %	1000 mm	B17066F_1
		2005 mm	B17066F_2
		3010 mm	B17066F_3
clear	91 %	1000 mm	B17066C_1
		2005 mm	B17066C_2
		3010 mm	B17066C_3

## RELATED PROFILES > FOR MAIN LIGHTING



**TRIADA**  
A04476

# Cover KA-13

Ref. B17066F, B17066C

## RELATED PROFILES > UNIVERSAL



**PAC-ALU**  
A04370



**STOS-ALU**  
A04369