

# WALL LIGHT 12W




## ΠΕΡΙΕΧΟΜΕΝΑ / CONTENTS


datasheet	1
manual	2

## ΚΩΔΙΚΟΣ / CODE

WL175-XX-XX-XX-XX-XX-XX-XX



## WALL LIGHT 12W (WL175) / Datasheet



### General information

Application	Indoor / Outdoor
Direction of mounting	Ceiling / Wall / Ground
LED	Cree / Osram
Wattage	12W
IP protection	IP67
Life time	50000 hrs
Warranty	3-5 years (*5 years upon request)
Origin	Greece
Visible dimensions (W×H×L)	50 × 50 × 50 mm

Material	Color	CCT	CRI	Beam angle	Voltage	Dimmable
Aluminium (01)	Anodised (AN)	2700K (27K)	Ra80 (80)	Diffuse (DF)	12VDC (V1)	Dim TRIAC 230VAC (D)
Inox (02)	Black (BL)	3000K (30K)	Ra90 (90)	8° (8D)	24VDC (V2)	No (L)
Brass (03)	White (WH)	4000K (40K)		15° (15D)	230VAC (V3)	
	RAL colors (RL)	5000K (50K)		20° (20D)	12/24V (V4)	
		6000K (60K)		25° (25D)	350mA (V5)	
		(R)/(G)/(B)/(A)		36° (36D)	500mA (V6)	
		RGB (C1)		45° (45D)	700mA (V7)	
				60° (60D)		
				80° (80D)		




Δημιουργία Κωδικού προϊόντος / Product Code generator

**WL175 - material - color - CCT - CRI - beam angle - voltage - dimmable**

(ex. WL175-01-AN-27K-80-8D-V3-D for Wall Light 12W Aluminium Anodised 1W 2700K Ra80 8° 230VAC Dimmable)

## WALL LIGHT 12W / Manual

1. ΠΡΟΕΤΟΙΜΑΣΙΑ ΓΙΑ ΕΦΑΡΜΟΓΗ ΣΤΟΝ ΤΟΙΧΟ / PREPARATION FOR WALL APPLICATION
2. ΤΟΠΟΘΕΤΗΣΗ ΒΑΣΗΣ ΣΤΟΝ ΤΟΙΧΟ / APPLICATION OF BASE ON WALL
3. ΚΑΝΕΤΕ ΤΗΝ ΗΛΕΚΤΡΙΚΗ ΣΥΝΔΕΣΗ / MAKE THE ELECTRICAL CONNECTION
4. ΤΟΠΟΘΕΤΗΣΗ ΤΟΥ ΦΩΤΙΣΤΙΚΟΥ / PLACE THE LUMINAIRE



4. Εφαρμογή στον τοίχο /  
Application on the wall

Εφαρμόστε το φωτιστικό στην τοποθετημένη βάση και βιδώστε το πάνω της με δεξιόστροφη περιστροφή μέχρι να σταθεροποιηθεί. /  
Apply the lamp to the mounted base and tighten it with a clockwise rotation until it is firmly stabilized on the base.

